PDC F-830 MURACULON C1187 352c MINT GREEN

Safety Data Sheet
Prepared according to Federal Register / Vol. 77, No. 58 / Worder, March 28, 2012 / Fulles and Regulations Chronic symptoms

Suspected of causing cancer, Suspected of damaging fertility, Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

No additional information available. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures Suitable extinguishing media Extinguishing media

Special hazards arising from the substance or mixture Foam. Carbon dioxide. Dry chemica

Precautionary measures fire Advice for firefighters Reactivity

Explosion hazard

Firefighting instructions

No dangerous reactions known under normal conditions of use Heating may cause an explosion.

Highly flammable liquid and vapour.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, furnes, smoke and poducts of combustion.

Do not enter fire area without proper protective equipment, including respiratory protection. This material is flammable and may be ignited by heat, sparks, or static electricity.

SECTION 6: Accidental release measures

Other information

Protection during firefighting

Personal precautions, protective equipment and emergency procedures Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

Evacuate unnecessary personnel. Wear Protective equipment as described in Section 8.

Emergency procedures

Protective equipment

Protective equipment

For emergency responders

6.1.1. For non-emergency personnel

General measures

Wear suitable protective clothing, gloves and eye or face protection, Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters, Avoid release to the environment

For containment Methods and material for containment and cleaning up

Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.

Soak up split with inert colific such as day or diatonaceous earth as soon as possible. Sweep or shovel split into appropriate cours are also provided and its container must be disposed of in a safe way, and as per local legislation.

See Sections 8 and 13. Reference to other sections Methods for cleaning up

SECTION 7: Handling and storage Precautions for safe handling Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and vater before acting, drinking or smoking and when leaving work. Keep away from sources of ignition - No smoking.

7.2.

Conditions for safe storage, including any incompatibilities

: Keep the container lightly closed. Store in a dry, cool and well-venifiated place. Keep away

from lightlons sources.

Storage conditions

SECTION 8: Exposure controls/personal protection 8.1. Control parameters Acetone (67-64-1)
ACGIH TWA (ppm)
ACGIH STEL (ppm)
OSHA PEL (TWA) (mg/m²)

PDC F-830 MURACULON C1187 352c MINT GREEN 750

3/10

9/1/2016

PDC F-830 MURACULON C1187 352c MINT GREEN

Safety Data Sheet
Prepared according to Federal Regulators
Prepared according to Federal Regulators
Prepared according to Federal Regulators

Acetone (67-64-1) OSHA PEL (TWA) (ppm)	1000
OSHA PEL (STEL) (mg/m²)	2400 (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors)
OSHA PEL (STEL) (ppm)	1000
Toluene (108-88-3)	
ACGIH TWA (ppm)	20
Remark (ACGIH)	Visual impair, female repro;
Methyl ethyl ketone (78-93-3)	The state of the s
ACGIH TWA (ppm)	200
ACGIH STEL (ppm)	300
OSHA PEL (TWA) (mg/m²)	590
OSHA PEL (TWA) (ppm)	200
OSHA PEL (STEL) (mg/m²)	885
OSHA PEL (STEL) (ppm)	300
Xylenes (o-, m-, p- isomers) (1330-20-7)	
ACGIH TWA (ppm)	100
ACGIH STEL (ppm)	150
OSHA PEL (TWA) (mg/m²)	435
OSHA PEL (TWA) (ppm)	100
OSHA PEL (STEL) (mg/m²)	655
OSHA PEL (STEL) (ppm)	150
Stoddard solvent (8052-41-3)	
ACGIH TWA (ppm)	100
Remark (ACGIH)	CNS impairment; Eye, skin, and kidney damage;
OSHA PEL (TWA) (mg/m²)	2900
OSHA PEL (TWA) (ppm)	500
Ethylbenzene (100-41-4)	
ACGIH TWA (ppm)	20
Remark (ACGIH)	upper respiratory tract irritation; kidney damage
OSHA PEL (TWA) (mg/m*)	435
OSHA PEL (TWA) (ppm)	100
OSHA PEL (STEL) (mg/m*)	545
OSHA PEL (STEL) (ppm)	125
Titanium dioxide (13463-67-7)	
ACGIH TWA (mg/m²)	10
OSHA PEL (TWA) (mg/m³)	15 total dust
Cumene (98-82-8)	
ACGIH TWA (ppm)	50
OSHA PEL (TWA) (mg/m²)	245
OSHA PEL (TWA) (ppm)	50
Methyl ethyl ketoxime (96-29-7)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

Exposure controls

Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

PDC F-830 MURACULON C1187 352c MINT GREEN

4/10

Performix GREEN Safety Data Sheet Prepared according to Federal Regulator / Vo. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Supersodes: 1021/2015 Version: 1.0 Version: 1.0 PDC F-830 MURACULON C1187 352c MINT

PDC F-830 MURACULON C1187 352c MINT GREEN

Product code Product form

Product identifier

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet

Plasti Dip International, Inc. 3920 Pheasant Ridge Drive Blaine, MN 55449 Phone - (763) 785-2156

Emergency number Emergency telephone number

CHEMTREC: 1-800-424-9300 (US); 703-527-3887 (International)

SECTION 2: Hazards identification

Classification of the substance or mixture

Flam. Liq. 2 H225 Skih irft 2 H315 Eye Imt. 2A H319 Skih Sens. 1 H317 Carc. 2 H351 Repr. 2 H351 STOT SE 3 H336 STOT RE 2 H373 Asp. Tox. 1 H304 GHS-US classification

GHS-US labelling

Label elements

Hazard pictograms (GHS-US)

Hazard statements (GHS-US) Signal word (GHS-US)

Precautionary statements (GHS-US)

Danger

H225 - Highly flammable liquid and vapour
H242 - Hagh of half if avallowed and enters airways
H316 - Causes shir initiation
H317 - May senue an allegic shir reaction
H319 - Causes soft initiation
H317 - May senue an allegic shir reaction
H319 - Causes soft causing cancer
H351 - Suspecied of damagin fertility or the unborn child
H372 - May reause damage to organs (central nervous system, hearing organs) through proceed or the period of the process of causing fertility or the unborn child
H372 - May cause damage to organs (central nervous system, hearing organs) through proceed or repeated exposure processes or the processes of the proces

Page 1

9/1/2016 PDC F-830 MURACULON C1187 352c MINT GREEN

PDC F-830 MURACULON C1187 352c MINT GREEN

Safety Data Sheet
Prepared according to Federal Register/Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rinse skin with wateris hower

Post-F340. If IN INFALED. Remove person to fresh air and keep comfortable for breathing
P304-F340. IF IN INFALED. Remove person to fresh air and keep comfortable for breathing
p304-F340. IF IN INFALED. Remove person to fresh air and keep comfortable for several minutes. Remove
contact lenses, if present and easy to do. Continue misting
p312- Cell a POISON CENTER, a doctor if you feet unwell
p314- cell nected advice/airthion if you feet unwell
p314- de medical advice/airthion for passing to passing the several passing to passing the passing the passing the passing to passing the passing t

Other hazards

No additional information available
2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

Substance

Not applicable

Name	Product identifier	%
Acetone	(CAS No) 87-64-1	15-40*
Toluene	(CAS No) 108-88-3	10-30*
Methyl ethyl ketone	(CAS No) 78-93-3	7-13
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	5-10
Titanium dioxide	(CAS No) 13463-67-7	1-5*
Ethylbenzene	(CAS No) 100-41-4	1-5*
Methyl ethyl ketoxime	(CAS No) 96-29-7	<= 0.1*
Cumene	(CAS No) 98-82-8	<0.1*
Stoddard Solvent	(CAS No) 8052-41-3	< 0.1*

"In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade-secret

SECTI	SECTION 4: First aid measures		
4.1.	Description of first aid measures		
First-aid	First-aid measures general	 = Q =	If exposed or concerned, get medical attention/ladvice. Show this safety data sheet to the doctor in attendance. Wash contaminated diching before re-use. Never give anything to an unconscious person.
First-aid	First-aid measures after inhalation	 ਜ = ਜ	IF INHALED: Remove to feesh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
First-aid	First-aid measures after skin contact	 e =	IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
First-aid	First-aid measures after eye confact	3 ॡ ॹ	IF IN LYTES immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue trissing.

Most important symptoms and effects, both acute and delayed

First-aid measures after ingestion First-aid illeasures alter eye cultiaci

		, M. J.	
causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to	reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of	: May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin	

IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

Symptoms/injuries after inhalation

May cause drowsiness or dizziness.

Causes skin imitation. May cause an allergic skin reaction.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

Symptoms/injuries after skin contact Symptoms/injuries after eye contact Symptoms/injuries after ingestion

9/1/2016 PDC F-830 MURACULON C1187 352c MINT GREEN 2/10

PDC F-830 MURACULON C1187 352c MINT GREEN Safety Data Sheet Prepared recording to Federal Regulator/ Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations Other adverse effects

: No data available.

Other adverse effects

Waste treatment methods

Waste treatment methods

Waste disposal recommendations

Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

UN-No.(DOT) DOT NA no. Transport document description In accordance with DOT

Proper Shipping Name (DOT)

: UN1139 Coaling solution (Contains: Accione, Methyl Ethyl Ketone, Toluene), 3, II : 1139

: UN1139

Department of Transportation (DOT) Hazard Classes Coating solution
 Contains: Acetone, Methyl Ethyl Ketone, Toluene
 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

: 3 - Flammable fiquid

Hazard labels (DOT)



Packing group (DOT) : II - Medium Danger DOT Quantity Limitations Passanger aircraft/rail : 5 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L CFR 175,75)

DOT Vessel Stowage Location : B-0

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carring a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Other information Additional information

No supplementary information available.

No additional information available,

Air transport

No additional information available,

SECTION 15: Regulatory information 15.1. US Federal regulations

PDG F-933 MURACULON C1187 352c MINT GREEN
All chemical substances in this product are fisted in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory or are exemp!
SARA Socilon 311/312 Hazard Classes
Delayed (chronic) health hazard.

CERCIARO	Acetone (67-64-1)	Immediate (acute) health hazard Fire hazard

CERCLARQ	5000 IN
Cooling of the Coolin	0000
Section 313	Not Listed on US SARA Section 313
Toluene (108-88-3)	
CERCLA RQ	1000 15
Section 313	1000 10
	Listed on US SARA Section 313

PDC F-830 MURACULON C1187 352c MINT GREEN

PDC F-830 MURACULON C1187 352c MINT GREEN

Safety Data Sheet
Prepared according to Federal Replater / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 313	CERCLA RO	Methyl ethyl ketone (78-93-3)	Section 313	CERCLA RQ
Not Listed on US SARA Section 313	5000 lb		Listed on US SARA Section 313	1000 lb
			NO.	

CERCLA RQ	100 lb
Section 313	Listed on US SARA Section 313

15.2. International regulations
No additional information available

WARNING! This product contains cher 15.3. US State regulations

No	Proposition 65 - Cardinogens List	Methyl alcohol (67-56-1)	Tes	U.S California - Proposition 65 - Carcinogens List	Cumene (98-82-8)	100	Yos	Carcinogens List	Proposition 65 -	Benzone (71-43-2)	ses	U.S California - Proposition 65 - Carcinogens List	Titanium dioxide (13463-67-7)	iga	U.S California - Proposition 65 - Carcinogens List	Ethylbenzene (100-41-4)	No	U.S California - Proposition 65 - Carcinogens List	Toluene (108-88-3)
Yes	U.S California - Proposition 65 - Developmental Toxicity		No	U.S California - Proposition 65 - Developmental Toxicity		Tes	V.	Developmental Toxicity	U.S California -		No	U.S California - Proposition 65 - Developmental Toxicity	-67-7)	Z	U.S California - Proposition 65 - Developmental Toxicity		Yes	U.S California - Proposition 65 - Developmental Toxicity	
No o	U.S California - Proposition 65 - Reproductive Toxicity - Female		No.	U.S California - Proposition 65 - Reproductive Toxicity - Female		Z		Reproductive Toxicity -	U.S California -		No	U.S California - Proposition 65 - Reproductive Toxicity - Famale		8	U.S California - Proposition 65 - Reproductive Toxicity - Female		No	U.S California - Proposition 65 - Reproductive Toxicity - Female	
No	U.S California - Proposition 65 - Reproductive Toxicity - Male		No	U.S California - Proposition 65 - Reproductive Toxicity - Male		Yes		Proposition 65 - Reproductive Toxicity -	U.S California -		No	U.S California - Proposition 65 - Reproductive Toxicity - Male		No.	U.S California - Proposition 65 - Reproductive Toxicity - Male		No	U.S California - Proposition 65 - Reproductive Toxicity - Male	
47,000 (inhalation) 23,000 (oral)	Maximum allowable dose level (MADL)		Not available	Non-significant risk level (NSRL)		13 (inhalation) 6.4 (oral) µg/day 49 (inhalation) 24 (oral) µg/day	level (MADL)	risk level (NSRL) Maximum	No significance		Not available	No significance risk level (NSRL)		54 (Inhalation) 41 (oral) µg/day	No significance risk level (NSRL)		7000 µg/day	Maximum allowable dose level (MADL)	

PDC F-830 MURACULON 01187 3526 MINT GREEN

8/10

PDC F-830 MURACULON C1187 352c MINT GREEN

Personal protective equipment

Safety Data Sheet
Prepared according to Federal Regulator / Vol. 77, No. 55 / Monday, March 26, 2012 / Rules and Regulators
Prepared according to Federal Regulators Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.

Hand protection

Use gloves chemically resistant to this material when protonged or repeated contact could cocur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove cocur. Gloves should be classified under Standard EN 374 or ASTM f1296. Suggested glove materials are: Neoprene, Nitrilabulacione rubber, Poyethlylene, Ethyl vrnyl alcohol lammate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove

Skin and body protection

Respiratory protection

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions, in case of intedequate verbilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type AZ). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure

SECTION 9: Physical and chemical properties Information on basic physical and chemical properties

Physical state Odor Threshold Flammability (solid, gas) Decomposition temperature Auto-ignition temperature Flash point Boiling point Freezing point Melting point Relative evaporation rate (butylacetate=1) No data available
-20 °C (-4 °F) TCC
No data available Characteristic. Solvent No data available

Relative vapour density at 20 °C Vapour pressure 185 mm Hg @ 20 °C Heavier than air (Air = 1)

Log Kow Lag Pow Solubility Relative density No data available No data available 0.89 - 0.91 (H2O = 1) slightly soluble in water

Oxidising properties Explosive limits Explosive properties Viscosity, dynamic Viscosity, kinematic No data available

No data available No data available No data available 1 - 12.8 vol %

Other information

44 - 45 % 72-76 % Volatile

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

Chemical stability

Stable under recommended handling and storage conditions (see section 7)

None known. 10.3. Possibility of hazardous reactions

PDC F-830 MURACULON C1187 352c MINT GREEN

5/10

9/1/2016

PDC F-830 MURACULON C1187 352c MINT GREEN

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rafes and Regulations

Conditions to avoid

Ignition sources. Heat. Sparks. Open flame. Static electricity

Incompatible materials

Strong acids. Strong bases, Strong oxidizing agents, selected amines with alkali metals and halogens

Carbon oxides (CO, CO₂). Hazardous decomposition products

SECTION 11: Toxicological information

Acute toxicity Information on toxicological effects

Skin corrosion/irritation Serious eye damage/irritation Causes serious eye irritation. Causes skin irritation

Not classified

Respiratory or skin sensitisation May cause an allergic skin reaction.

Not classified

Carcinogenicity Germ cell mutagenicity

 Carcinogenic to humans
 Carcinogenic to humans
 Carcinogens Suspected of causing cancer.

Vinyl chloride (75-01-4) IARC group Vinyl acetate (108-05-4) IARC group IARC group Ethylbenzene (100-41-4) IARC group
National Toxicology Program (NTP) Status Benzene (71-43-2) Titanium dioxide (13463-67-7) National Toxicology Program (NTP) Status Cumene (98-82-8) 1 - Carcinogenic to humans 2 - Known Human Carcinogens 2B - Possibly carcinogenic to humans 2B - Possibly carcinogenic to humans 2B - Possibly carcinogenic to humans 2B - Possibly carcinogenic to humans

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated May cause damage to organs (cnetral nervous system, hearing organs) through prolonged or

Symptoms/injuries after inhalation Aspiration hazard May be fatal if swallowed and enters airways.

Symptoms/injuries after skin contact May cause drowsiness or dizziness.
Causes skin imitation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact Causes serious eye irritation.

Symptoms/Injuries after ingestion May be fatal if swallowed and enters airways.

Suspected of causing cancer, Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

Toxicity

Ecology - general No information available

Persistence and degradability

Persistence and degradability PDC F-830 MURACULON C1187 352c MINT GREEN No information available

PDC F-830 MURACULON C1187 352c MINT GREEN
No info Bioaccumulative potential

PDC F-830 MURACULON C1187 352c MINT GREEN

Recology - soil

No information available Mobility in soil

PDC F-830 MURACULON C1187 352c MINT GREEN

6/10

PDC F-830 MURACULON C1187 352c MINT GREEN

Safety Data Sheet
Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3 µg/day	No	No	No	Yes
No significance risk level (NSR	U.S California - Proposition 65 - Reproductive Toxicity - Male	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Carcinogens List

Sodium metabisulfite (7881-97.4) Sodium metabisulfite (7881-97.4) U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List U.S Massachusetts - Right To Know List
Polyvinyl chloride (9002-86-2) II S New Jersey - Right to Know Hazardous Substance List
Vinyl chloride (75-01-4) U.S Masachhaetts. Right To Know List U.S Masachhaetts. Right to Know hazardous Substance List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Vinyl acetate (109-05-4) U.S Masachusetts - Right To Know List U.S Mesachusetts - Right to Know hazardous Substance List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Xylenes (o-, m-, p- Isomers) (1330-20-7) U.S MasaChisatts - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know hot Environmental Hazard List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Methyl ethyl ketone (78-93-3) U.S Masachusatts - Right to Know List U.S Mesachusatts - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List
Cumene (98-92-8) U.S Masachusetts - Right To Know List U.S Mesachusetts - Right to Know hazardous Substance List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Ethylbenzene (100-41-4) U.S., - New Jersey - Rejht to Know Hazzardous Substance List U.S., - Pennsylvania - RTK (Right to Know) - Environmental Hazzard List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazzard List
Toluene (198-89-3) U.S Massachusetts - Right To Know List U.S New Jessey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S Pennsylvania - RTK (Right to Know) List
Methyl alcohol (67-55-1) U.S Massachusetts - Right To Know List U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Benzene (71-43-2) U.S Massachusetts. Right To Know List U.S New Jersey. Right to Know Hazardous Substance Lisl U.S New Jersey. Right to Know Hazardous Substance Lisl U.S Pennsylvania - RTK (Right to Know). Special Hazardous Substances U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Acetone (87-64-1) U.S Massachusetts - Right To Know List U.S Mex-Jersey-Right 16 Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List

PDC F-830 MURACULON C1187 352c MINT GREEN

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Stoddard solvent (8052-41-3)
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List Due to pigments may contain up to 9 Proprietary Non-Hazardous Ingredients (Proprietary CAS) U.S. - Stale Right To Know List Titanium dioxide (13483-67-7)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List Barium suffate (7727-43-7)
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvaria - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List Silica, amorphous (7631-86-9)
U.S. New Jersey - Right to Know Hazardous Substance List
U.S. - Massachusets - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List Proprietary Inert
U.S. - State Right To Know List

SECTION 16: Other information Health NFPA reactivity NFPA fire hazard NFPA health hazard Other information Version 1.0 (16 Oct 2015) Version 2.0 (1 Sep 2016) HMIS III Rating lammability پ م د 3-t Bord exposure could cause serious temporary or residual injury even though prompt nedical attention was given.

4-t Vtill apidly or completely vaporize at normal pressure at the programment of the pr 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently. Author: LMG ed GHS complaint SDS ted classification/composi

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Physical

Personal Protection

PDC F-830 MURACULON C1187 352c MINT GREEN 9/10

9/1/2016

PDC F-830 MURACULON C1187 352c MINT GREEN

10/10

9/1/2016